



**Non-Toxic!  
Environmentally Safe!**

## **Directions For LayorCare Sealer Product Use**

### **LayorCare Neutral Seal (Water Based)**

- Depending on existing surface, clean area to be sealed with LayorCare's Pre-Treat Cleaner, Heavy Calcium Releaser or Multi-Blaster.
- Apply Neutral Seal with brush, roller or airless sprayer.
- Always use full strength--DO NOT DILUTE.
- Two coats are recommended. Allow to dry to touch before applying additional coats.
- Surface can be walked on after 1 hour.
- Let cure for 24 hours before applying standing water. (fountain, pool, spa)
- Product covers approximately 1000 sq ft per gallon per single coat application.
- Neutral Seal will last up to 3 years when properly maintained!

### **LayorCare Wet Look Seal (Water Based)**

- Allow newly grouted surfaces to cure for 48 hours before applying.
- Depending on existing surface, clean area to be sealed with LayorCare's Pre-Treat Cleaner, Heavy Calcium Releaser or Multi-Blaster.
- Rinse area and let dry completely.
- Apply Wet Look Seal with brush, roller or airless sprayer.
- Always use full strength--DO NOT DILUTE.
- Two coats are recommended. Allow to dry to touch before applying additional coats.
- Surface can be walked on after 3 hours.
- Let cure for 24 hours before applying standing water. (fountain, pool, spa)
- Product covers approximately 400 sq ft per gallon per single coat application.
- Wet Look Seal lasts up to 5 years when properly maintained!

### **LayorCare Paver Seal (Water Based)**

- Allow newly grouted surfaces to cure for 48 hours before applying.
- Depending on existing surface, clean area to be sealed with LayorCare's Pre-Treat Cleaner, Heavy Calcium Releaser or Multi-Blaster.
- Rinse area and let dry completely.
- For brick pavers apply immediately after installation.
- Paver Seal will bond the joint sand between the pavers to help prevent weather erosion.
- Apply Paver Sealer with brush, roller or airless sprayer.
- Always use full strength--DO NOT DILUTE.
- Two coats are recommended. Allow to dry to touch before applying additional coats.
- Surface can be walked on after 3 hours.
- Let cure for 24 hours before applying standing water. (fountain, pool, spa)
- Product covers approximately 400 sq ft per gallon per single coat application.
- Paver Seal lasts up to 3 years when properly maintained!

**WE REIGN. LET IT POUR.**