

SV Series

Commercial Locks



SV SERIES COMMERCIAL GRADE 2 CYLINDRICAL

SUGGESTED ARCHITECTURAL SPECIFICATIONS

Lockset will be SV Series from PDQ Industries, Inc., Leola, Pennsylvania. Lock will conform to ANSI A156.2, Series 4000, Grade 2, and U.L./U.L.C. Listed with a one-year manufacturer's limited warranty. Inside mounting plate

shall fit ANSI 161 cut-out. Lockset to be fully adjustable for 1-3/8" to 1-3/4" doors. Lock will accommodate keyways of major manufacturers.












SPECIFICATIONS – SV Series

FOR DOORS:	1-3/8" to 1-3/4" thick.
DOOR PREP:	Fits standard 161 door prep.
BACKSET:	2-3/4", 2-3/8", 5".
CASE:	Steel, yellow chromate plate.
FRONT:	2-1/4" x 1-1/8" or 2-1/4" x 1" / Stainless steel or wrought bronze.
STRIKE:	4-7/8" x 1-1/4" (ASA). "T" or "FL" Strike optional. Stainless steel or wrought bronze.
LATCHBOLT:	1/2" throw. Solid brass. Adjustable for beveled doors.
TRIM:	CQ ball knob. Stainless steel or wrought brass.
KEYS:	Two change keys per lock.
KEYWAYS:	Available in keyways of most major manufacturers.
CYLINDER:	Brass 6-pin cylinder keyed to 5 pins.
KEYING:	Can be MK, CMK, GMK, or CK. Available Zero Bitted (KO), Keyed Different (KD), Keyed Alike (KA). Can be keyed into existing masterkey systems of other manufacturers.
FINISHES:	US3(605), US10(612), US10B(613), US32(629), US32D(630).
CERTIFICATIONS:	➤ Complies with ANSI A156.2, Series 4000, Grade 2. ➤ U.L./U.L.C. Listed for "A" label (3 hour) single swing doors (4'0" x 8'0").
WARRANTY:	One-year limited warranty.

SV SERIES



SV SERIES COMMERCIAL GRADE 2 FUNCTION CHART

FUNCTION	FUNCTION NO.	INSIDE	OUTSIDE	FUNCTION DESCRIPTION	ANSI NO.
Storeroom	SV 115			<ul style="list-style-type: none"> Latchbolt operated from outside by key, inside by knob Outside knob is rigid at all times Inside knob always free for immediate exit Deadlocking (guarded) latchbolt 	F86-2
Entrance	SV 116			<ul style="list-style-type: none"> Latchbolt operated by both knobs Outside knob locked or unlocked by turn/push button Inside knob always free Pushing and turning button locks outside knob requiring use of key until button is manually unlocked Pushing button only locks outside knob until unlocked with key or inside knob is turned 	F81-2
Closet/ Communicating	SV 125			<ul style="list-style-type: none"> Blank plate outside Inner knob always free Deadlocking (guarded) latchbolt 	
Passage	SV 126			<ul style="list-style-type: none"> Latchbolt operated by both knobs 	F75-2
General Entrance	SV 137			<ul style="list-style-type: none"> Latchbolt operated by both knobs Key on either side locks or unlocks Deadlocking (guarded) latchbolt 	
Classroom, Storage	SV 148			<ul style="list-style-type: none"> Latchbolt operated from outside by knob except when locked from outside by key Latchbolt operated from inside by knob at all times Deadlocking (guarded) latchbolt 	F84-2
Exit or Twin Communicating	SV 150			<ul style="list-style-type: none"> Blank plate outside Key inside locks or unlocks inside knob No outside operation Deadlocking (guarded) latchbolt 	
Hotel Room	SV 161			<ul style="list-style-type: none"> Outside knob rigid at all times Latchbolt operated from outside by guest key, master key or grand master key, except when shut-out button is used Emergency key operates latchbolt at all times Outside is equipped with indicator pin Inside is always free Deadlocking (guarded) latchbolt 	F93-2
Bathroom Privacy	SV 176			<ul style="list-style-type: none"> Latchbolt operated by both knobs Push button in inside knob locks outside knob Inside knob or closing door releases button Emergency opening from outside 	F76-2
Patio	SV 177			<ul style="list-style-type: none"> Latchbolt operated by both knobs Push button in inside knob locks outside knob Inside knob or closing door releases button Deadlocking (guarded) latchbolt 	
Dummy	SV 211 SV 205			<ul style="list-style-type: none"> Single or double pull knob(s) One or both side(s) No mechanical operation Surface mounted (SV 211) 2-1/8" bored hole (SV 205) 	



PO Box 507 2754 Creek Hill Road Leola PA 17540

800 441 9692

717 656 4281

717 656 6892 Fax

www.pdqlocks.com