



Oil & water repellent sealer

Oil & water repellent sealer is water based, it imparts both water repellency and oil repellency to most masonry surfaces. The pores of the masonry remain open, allowing the masonry to breathe. Oil, grease, paint, etc. are easier to remove from surfaces that have been treated.

Recommended for;

- Treatment of floors of natural or synthetic stone, or unglazed ceramic tiles for easy care.
- Treatment of window sills and table tops of natural or synthetic stone, or fibrous cement to avoid staining.
- Treatment of facades of natural or synthetic stone concrete or fibrous cement in order to allow easier removal of dirt, grease, graffiti, posters, etc. from monuments, exterior and interior walls.
- Water, oil and dirt repellent treatment of low-porosity natural stone, e. g. marble, travertine and granite.

Surfaces treated with Oil & water repellent should be cleaned at once after contaminations with oil, grease or paint because paint in particular is very difficult to dissolve once the binder has fully hardened. Surfaces that have been cleaned and dried might need re-treating with the product.

Surfaces should be clean, dry, firm and free from oil or previously applied sealers or coatings. If required, surfaces can be washed with a strong detergent/degreaser and rinsed with water. Any cracked or damaged areas should be filled with cement based filler and allowed to cure & dry. Apply the product by brush, roller or airless sprayer, making sure that the surface is saturated. If solution is quickly absorbed apply a second coat at a rate that shows the product pooling on the surface. Any product remaining on the surface after 5 minutes should be wiped off. (So as to not create an uneven surface) REMOVE PRODUCT FROM AREAS YOU DO NOT WISH TO TREAT IMMEDIATELY WITH A DAMP CLOTH OR SPRAY. Do not apply if rain or extreme weather conditions are expected.

Coverage rate will vary from 2-10m² per litre/coat and always test a small area to ensure suitability of the product to your requirements. Shake/Stir well prior to use

Water repellence in 24 hours and full cure achieved in 7 days.

Physical Data – Milky white in appearance

- Solids content of < 10% by weight
- Specific gravity of 1.0 @ 20 °C
- pH of – 7
- Soluble in water
- No VOC content
- Non flammable

First Aid

Eyes Flush eyes with water for at least 15 minutes

Skin May cause irritation, Wash affected areas with soap and water.

Inhalation May cause irritation, Move subject to fresh air, if breathing is difficult, give oxygen.

Ingestion can cause gastrointestinal irritation, Give 2 glasses of water to drink to dilute.

Consult a Doctor. DO NOT INDUCE VOMITTING

Handling & Storage

Non-Hazardous according to criteria of Worksafe Australia.

The product is classified as a non-hazardous material. However, as with all chemical products good industrial hygiene procedures should be followed when using this product.

Wear suitable gloves & goggles and use in well ventilated areas.

Store in well ventilated area and keep container sealed and away from excessive heat and out of direct sunlight.

KEEP OUT OF REACH OF CHILDREN