



Water repellent sealer

Water repellent sealer is a water-based sealer, one application will provide a long lasting barrier to the ingress of water in bricks, concrete, render and all porous masonry products. The product is designed to penetrate into the capillaries of masonry surfaces and reduce the absorption of water, water-borne staining and stop efflorescence.

The sealer is Non-Toxic, will not peel or blister is UV and alkali stable and under normal circumstances will not significantly alter the appearance of the masonry products. However it is strongly recommended that a test be carried out prior to application as some masonry products have pigments that may be highlighted after application

Features

- Good depth of penetration • High resistance to alkalis • Rapid development of water repellency
- Provides good adhesion for paints • Water-based and environmentally compatible

Surfaces should be clean, dry, firm and free from oil or previously applied sealers or coatings. If required, surfaces can be washed with a strong detergent/degreaser and rinsed with water. Any cracked or damaged areas should be filled with cement based filler and allowed to cure & dry. Apply Paving water repellent sealer by brush, roller or airless sprayer, making sure that the surface is saturated. If solution is quickly absorbed apply a second coat at a rate that shows the product pooling on the surface. Any product remaining on the surface after 5 minutes should be wiped off. (So as to not create an uneven surface) REMOVE PRODUCT FROM AREAS YOU DO NOT WISH TO TREAT IMMEDIATELY WITH A DAMP CLOTH OR SPRAY. Do not apply if rain or extreme weather conditions are expected.

Coverage rate will vary from 2-10m² per litre/coat and always test a small area to ensure suitability of the product to your requirements. Shake/Stir well prior to use

Water repellence in 24 hours and full cure achieved in 7 days.

- Physical Data – Milky white in appearance
- Solids content of < 10% by weight
 - Specific gravity of 1.0 @ 20 °C
 - pH of 7 – 8
 - Soluble in water
 - No VOC content
 - Non flammable

First Aid

Eyes Flush eyes with water for at least 15 minutes

Skin May cause irritation, Wash affected areas with soap and water.

Inhalation May cause irritation, Move subject to fresh air, if breathing is difficult, give oxygen.

Ingestion can cause gastrointestinal irritation, Give 2 glasses of water to drink to dilute.

Consult a Doctor. **DO NOT INDUCE VOMITTING**

Handling & Storage

Non-Hazardous according to criteria of Worksafe Australia.

The product is classified as a non-hazardous material. However, as with all chemical products good industrial hygiene procedures should be followed when using this product.

Wear suitable gloves & goggles and use in well ventilated areas.

Store in well ventilated area and keep container sealed and away from excessive heat and out of direct sunlight.

KEEP OUT OF REACH OF CHILDREN