



Drag Conveyors



- Heavy-gauge, galvanized steel construction ensures Sukup Drag Conveyors will last for years to come.
- Dust-proof and weather-tight covers.
- Shaft, sprocket and bearings can be removed as one piece.
- ½" UHMW flights prevent steel-to-steel contact.



Sukup Manufacturing Co. ■ www.sukup.com

Box 677 ■ 1555 255th St. ■ Sheffield, IA 50475-0677 ■ Phone: 641-892-4222
Fax: 641-892-4629 ■ Email: info@sukup.com

Six Distribution
Centers
To Serve You
Better

Arcola, IL 61910
980 E. State Rd.
Phone: 217-268-3026
Fax: 217-268-3522

Aurora, NE 68818
1705 Hwy. 34 E.
Phone: 402-694-5922
Fax: 402-694-5921

Defiance, OH 43512
7724 Rte. 66 N.
Phone: 419-784-9871
Fax: 419-784-9872

Jonesboro, AR 72403
5917 E. Johnson Ave.
Phone: 870-932-7547
Fax: 870-933-8946

Cameron, MO 64429
7426 NE 352nd St.
Phone: 816-649-2226
Fax: 816-649-2225

Watertown, SD 57201
2701 Piper Ave.
Phone: 605-882-6697
Fax: 605-884-0467



Drag Conveyor Specifications

Model	Width	Depth	Conveyor Speed			
			100 ft/min.	125 ft/min.	150 ft/min.	180 ft/min.
1209	12"	9"	1903	2379	2854	3425
1213	"	13"	3334	4168	5002	6002
1217	"	17"	4829	6036	7244	8693
1609	16"	9"	2525	3156	3787	4545
1613	"	13"	4425	5531	6637	7965
1617	"	17"	6408	8010	9612	11,535
2109	21"	9"	3225	4031	4837	5805
2113	"	13"	5651	7064	8477	10,173
2117	"	17"	8185	10,231	12,277	14,733


* Capacities bu/hr. based on 45 lbs./ft.

Sukup Manufacturing Co provides the information contained within this brochure to assist you in choosing the optimal equipment for your situation. Many factors, such as grain variety, maturity levels, grain cleanliness, weather conditions and operation/management, can affect the performance of your equipment and results may vary. This information is calculated and is not a guarantee of product specifications or performance. Based on these factors, Sukup specifications should only be used as estimates, and not as a warranty, express or implied, of how a particular Sukup unit will perform under your operating conditions. Because we are continually improving Sukup products, changes may occur that may not be reflected in the specifications.



Standard Features

- Galvanized construction for long life.
- 10 gauge housings are standard.
- Bolted, removable bottom construction.
- Roller chain is engineered for each conveyor to maximize working load and prolong system life.
- ½" UHMW flights prevent steel-to-steel contact.
- UHMW return rollers std. - return rails optional.



Options

- Abrasion-resistant liners and bottoms.
- By-pass inlets with drive-over grating
- Drive-over dump hopper with drive-over grating
- Bend sections
- Reversing feature
- Intermediate discharge gates (manual, electric, pneumatic)

Head & Tail Sections

- Head shafts are turned, ground and polished.
- Shaft seals are 1/4" thick UHMW.
- Extended mount flange bearings on 9" tall conveyors.
- External mount pillow block bearings on 13" and 17" tall conveyors.
- Flame cut, hardened steel sprockets.
- Shaft, sprocket and bearings can be easily removed as one piece.
- End relief door with limit switch is optional.
- ACME threaded screws are used in the chain tension take-up system.

