Regain the freedom of your home



The Acorn 130 Stairlift

The Acorn 130 Stairlift is one of the most advanced and widely used stairlifts in the world, helping hundreds of thousands of people worldwide to safely and comfortably use their stairs and enjoy their homes again.

Every aspect of the Acorn 130 Stairlift has been designed to the highest standards of comfort and safety. Our years of experience have helped us to create a stairlift that is built purely with the end-user in mind.

The Acorn 130 Stairlift is powered by a maintenance-free DC powered battery pack, which ensures uninterrupted use, even in the event of a power outage.

With a built-in soft start and stop mechanism, the Acorn 130 provides a smooth and comfortable ride every time.

Another feature pioneered by Acorn is the on-board diagnostic control panel which alerts you to any potential problems before they arise, (e.g. the stairlift has accidentally been switched off or incorrectly parked).

The Acorn 130 Stairlift has also earned the prestigious Easeof-Use Commendation from the Arthritis Foundation, further proving how safe, comfortable and easy to use it is. When not in use, the Acorn 130 folds up, nice and easy, so that everyone can continue to use the stairs.

Also available:

- Hinged Rail for when a standard rail may present an obstruction at the foot of the stairs.
- Outdoor Stairlift fully weather-proofed for outdoor use.







Give your life a lift[®]

Enjoy the home you love



A wealth of features for your benefit



9 Hand-held remote controls allow users to 'call' or 'send' the lift up and down the staircase.

Dimensions	inch	mm
A Floor to top of footrest	3¾	95
B Top of footrest to top of seat	17 ½	445
C Top of seat to top of arms	9 ³ / ₄	250
D Top of arms to top of seat back	71/2	190
E Width between armrests (Wide arm version)	17½ (19½)	445 (495)
F Overall width	23¾	605
G Overall height	381/2	980
H Length of arms from seat back	181/2	470
I Length of seat base from seat back	17	435
J Length of footrest	123/4	325
K Width of footrest	121/4	310
L Front of footrest to stringer	221/2	570
M Back of seat to stringer	1/2	13
N Folded width	121/4	310
O Minimum width required to swivel at top	261/4	670
P Distance from front of rail to stringer (Wide arm version)	81/2 (91/2)	215 (240)

Specifications

Motor Power
Motor Output Speed
Method of Drive
Power Supply
Maximum Capacity
Track
Mains Supply

0.25KW (USA) No greater than 0.15 m/s (USA) Rack and Pinion 24V DC (battery) 300lbs (optional 350lbs) Extruded Aluminium 120V AC, 1.5 Amp Charger

Dealer Stamp





L



