

RF6

Dual Sealed Beam Rotating Beacon Light



Description

Tri Lite's RF6 beacon is our brightest 8" DC warning light. This light utilizes two rotating PAR 38 sealed beam lamps under a tough polycarbonate dome. The light is mounted on a heavy duty aluminum base to keep out the elements and prevent corrosion. This versatile light is perfect for warning applications, lighting effects or the indication of machine status. The RF6 can be ordered in a variety of dome colors. This top quality light is made in America and comes with Tri Lite's 12 month limited warranty.

Electrical Specifications

DC Voltage	12 or 24 VDC
DC Current	4.7 A at 12VDC
Estimated Lamp Life	300
Lamp Brightness	



Features

- Large powerful lamps.
- Attractive design.
- Heavy-duty aluminum base.
- Tough polycarbonate dome available in amber, blue, clear, red or green.
- Quite belt driven mechanism.
- Easily field serviceable.
- Available in 12 or 24 VDC.
- Optional magnetic mounting kit.

The RF6 provides an attractive and reliable solution for many situations and is an excellent choice for a wide range of applications including:

- Entertainment and theatre lighting
- Industrial alerts
- Machine status indication
- Architectural warning
- Access control indication

Physical Specifications

Height	.91/8"
Diameter	
Flashes per Minute	80 - 90
Shipping Weight	8 lbs
Shipping Volume	0.85 ft^3


: 800-741-1258 **:** 866-709-2802

P.O. Box 15, Ashley Oh 43003





RF6 Beacon



Model Number Information

Model

Product Number

12 VDC Model RF6-12P/* 24 VDC Model RF6-24P/*

* Specify Dome Color **A**-Amber **B**-Blue **C**-Clear **G**-Green **R**-Red

Replacement Part Information

Part	Part Number	
Amber Dome	200514	
Blue Dome	200512	
Clear Dome	200529	
Green Dome	200526	
Red Dome	200513	
Lamp	420420	
Drive Belt	800570	



€ : 800-741-1258 **₹** : 866-709-2802

: Sales@loadingdocksupply.com: www.Loadingdocksupply.com

P.O. Box 15, Ashley Oh 43003







Using gasket as a template, mark desired location of center hole and 3 mounting holes. Use 3/16" drill for 3 outside holes and 7/16" drill for center hole. Insert rubber grommet in center hole.

Remove dome and operating mechanism from light. Place gasket and housing in desired location on vehicle over newly drilled holes. Fasten housing to roof of vehicle with included screws and washers. To assure good electrical ground, place one mounting screw through ground eyelet on black ground lead.

Replacement Parts

110 01000111011110				
<u>PART</u>	DESCRIPTION	<u>RF-6</u>	<u>RF-64</u>	
DOME	AMBER	200523	200536	
	RED	200522	200535	
	BLUE	200527	200534	
	GREEN	200526	200537	
	CLEAR	200529	200533	
LAMPS	12V	420420	420420	
	24V	420610	420610	
MOTOR	12V	553040 (163040T)	553040 (163040T)	
	24V	553051 (163051T)	553051 (163051T)	
DRIVE BELTS	2 REQ'D	800570	800570	
DOME RET. RING	COMPLETE	553508 (163508T)	553509 (163509T)	
MTG. GASKET	AS SUPPLIED	810104	810103	
HDWR.MTG.KIT	AS SUPPLIED	550026 (160026T)	550026 (160026T)	
MAGNETIC MTG. KIT -W-CIGAR LIGHTER PLUG	12V ONLY	RFMAG	RFMAG	

All domes are shatterproof polycarbonate material.



